



## *Explorer TB*

### **The ideal tractor for specialists in the field.**

Explorer TB is unlike anything else in its class: an extremely versatile, practical and potent multirole machine that's ready to take on even the toughest job. Offered as 105 and 115 variants, Explorer TB tractors are designed for the farmer with specialised needs. The unbeatable choice for olive groves, widely spaced fruit orchards, greenhouses and mountain terrain with its limited overall height, low centre of gravity and sturdy construction for working with heavy duty implements. FARMotion 4-cylinder turbo-intercooled engines with common rail injection deliver immediately responsive power in all conditions.

EXPLORER TB:  
105 | 115



**SAME**

# Explorer TB

105

115

ENGINE			
Emissions		Stage III B	Stage III B
Manufacturer		SDF	SDF
Series		FARMotion	FARMotion
Cylinders/Capacity	No./cc	4/3849	4/3849
Induction		TI	TI
Max. power (ECE R120) @ 2000 rpm	kW/HP	75 / 102	83 / 113
Rated power (ECE R120) @ 2200 rpm	kW/HP	71,5 / 97	79 / 107
Max. torque at 1600 rpm	Nm	408	435
Electronic engine governor system		●	●
Fuel tank capacity	litres	85	85
SHUTTLE			
Mechanical Reverse Shuttle (LS)		●	●
Hydraulic PowerShuttle and Stop&Go system (GS)		○	○
MECHANICAL GEARBOX			
5 speed gearbox, 10+10 (40 km/h)		●	●
5 speed gearbox, 20+20 with underdrive and creeper gear (40 km/h)		○	○
HI-LO POWERSHIFT GEARBOX			
5 speed gearbox, 20+20 (40 km/h)		○	○
5 speed gearbox, 40+40 with underdrive and creeper gear (40 km/h)		○	○
REAR PTO			
Electrohydraulic control		●	●
PTO 540/540ECO		●	●
PTO 540/540ECO/1000/1000ECO		○	○
Ground speed PTO		○	○
1000 front PTO		○	○
FRONT AND REAR AXLE			
Electrohydraulically selected four wheel drive		●	●
Electrohydraulically selected differential lock		●	●
BRAKES AND STEERING			
Independent parking brake		●	●
Hydraulic trailer braking		○	○
Hydrostatic steering with independent pump		●	●
SDD rapid steering system		○	○
LIFT			
Mechanical rear lift		●	●
Rear lift capacity	kg	3600	3600
Rear lift capacity with supplementary lift cylinders	kg	4525	4525
Front lift		○	○
Front lift capacity	kg	2100	2100
HYDRAULIC SYSTEM			
Hydraulic System	l/min	55	55
Rear hydraulic auxiliary distributors	n° of ways	4 / 6	4 / 6
PLATFORM			
Digital display		●	●
Telescopic steering column		●	●
Folding rear ROPS		●	●
Folding front ROPS		○	○
DIMENSIONS AND WEIGHTS			
Max. length	mm	4117	4117
Min./ max. width (standard configuration)	mm	1939 / 2101	1939 / 2101
Max. height at cowl	mm	1520	1520
Wheelbase	mm	2400	2400
Weight with ROPS	kg	3500	3500
Maximum permissible load	kg	6200	6200

- STD
- OPT
- Not available

Area dealer

To find out more, visit [same-tractors.com](http://same-tractors.com)  
or talk to you dealer.

SAME is a brand of 

